Tender text

IN-164R/5

Single-channel diversity UHF PLL receiver,

with REMOSET technology.

• Bandwidth: 36 MHz
• 124 preset channels in 6 channel groups
• Up to 20 channels intermodulation-free
• REMOSET technology for synchronising receiver with transmitter
• Auto-scan function
• Pilot tone squelch and noise squelch
• Level of audio signal can continuously be adjusted
• 20 dB attenuator
• LED display for indicating RF level and AF level
• Backlit display with status indications, e.g. battery status of the transmitter, receiver channel/receiver group, audio level/RF level, mute, lock and active antenna
• Power supply for optional antenna booster UB-900I directly via antenna inputs
• 482 mm (19") mounting frame DR-900SET allows for 1 RS rack installation of 2 x IN-164R/5 and is available at option

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

Specifications:

General information	
Description	wireless receiver
Carrier frequency range	506-542 MHz
Audio frequency range	40-18,000 Hz
Channels	1
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	100 mV XLR, 100 mV jack
Power supply receiver	via encl. power supply
Width receiver	210 mm
Height receiver	42 mm
Depth receiver	195 mm
Weight receiver	525 g
Connections receiver	XLR, bal., 6.3 mm jack, bal.

Brand: JTS

Type: IN-164R/5

Quantity: 1

Packing dimensions (W x H x L): 0.135 x 0.225 x 0.28 m

Gross weight: 1.149 kg

Net weight: 0.686 kg

Item weight (w/o accessories): 0.525 kg