

CS-W4C/5

Order No. 100017



CS-W4C/6

Order No. 1000124



4-channel diversity UHF PLL wideband receivers for conference system

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- Conference modes: override, priority and open mode
- RF output and mains voltage output for easily cascading up to 10 x CS-W4C/5 receiver without additional splitter
- REMOSET technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute

- Backlit display for indicating the status, e.g. for group/channel, frequency, battery, antenna A/B
- LED for indicating RF level and AF level
- Link connections
- Trigger output
- 482 mm (19") rack installation, 1 RS

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



Model	CS-W4C/5	CS-W4C/6
Description	receiver unit	receiver unit
Carrier frequency range	506-542 MHz	626-662 MHz
Audio frequency range	60-16,000 Hz	60-16,000 Hz
THD	< 0.6%	< 0.6%
Dynamic range	> 105 dBA	> 105 dBA
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 316 mV/600 Ω jack	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 316 mV/600 Ω jack
Power supply receiver	~ 110-240 V/50-60 Hz/20 VA	~ 110-240 V/50-60 Hz/20 VA
Dimensions receiver	485 x 45 x 260 mm	485 x 45 x 260 mm
Weight receiver	2.4 kg	2.4 kg

CS-W4T/5

Order No. 1000018



CS-W4T/6

Order No. 1000122



UHF PLL microphone desk stand transmitters for the chairperson

- Back-electret microphone cartridge, supercardioid polar pattern
- 400 mm gooseneck, removable
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity
- Switchable transmitting power
- Low cut function
- Automatic switch-off

- Lock function
- LCD for indicating group/channel, audio level and battery status

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



Model	CS-W4T/5	CS-W4T/6
Polar pattern	supercardioid	supercardioid
System	back electret	back electret
Carrier frequency range	506-542 MHz	626-662 MHz
Transmitting power	10/50 mW	10/50 mW
Operating time	≈ 25 h	≈ 25 h
Audio frequency range	60-16,000 Hz	60-16,000 Hz
Power supply	2 x batt. AA size, alkaline (not supplied)	2 x batt. AA size, alkaline (not supplied)
Dimensions	138 x 29 x 116 mm (console housing)	138 x 29 x 116 mm (console housing)
Weight	720 g	720 g

W4-CH12

Order No. 1000020



Transport case with integrated charging function, for UHF PLL microphone desk stand transmitter CS-W4T/5.

- For simultaneously charging rech. batteries of up to 12 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 5 hours
- Each slot with LED for indicating battery charging status

- Mechanical reverse polarity protection
- Protection against overload, short-circuit and deep discharge
- Supplied with 24 x NiMH rech. battery AA size (2,000 mAh)
- Butterfly locks and recessed drop handles
- Stackable

- Matching transport case cover W4-CH12/COVER is available at option, please order separately
- Supplied w/o cover and devices.**



W4-CH1

Order No. 1000019



Charging station, for a UHF PLL microphone desk stand transmitter CS-W4T/5.

- Average charging time, depending on condition of rechargeable batteries used: approx. 3 hours
- LED for indicating batt. charging status
- Mechanical reverse polarity protection

- Protection against overload, short-circuit and deep discharge
 - Supplied with 2 x NiMH rech. battery (2,000 mAh)
- Supplied w/o devices.**



W4-CH12/COVER

Order No. 1000021



Transport case cover

- Suitable for transport case with integrated charging function W4-CH12.

