

RU-G3TH/5

Order No. 0259843

Hand-held UHF PLL transmitter with condenser cartridge

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 comp. preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Pilot tone squelch and noise mute
- Lock function/mute function
- Special design to reduce handling noise, structure-borne noise and acoustic feedback
- Backlit LCD for indicating battery status and low battery alert, switchable transmitting power

Model	RU-G3TH/5
Transmission method	wireless
Polar pattern	cardioid
System	condenser
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Audio frequency range	50-18,000 Hz
Max. sound pressure	140 dB
Dimensions	Ø 50 mm x 253 mm
Weight	780 g

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



RU-G3TB/5

Order No. 0259842

UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Backlit LCD for indicating battery status and low battery alert
- Switchable transmitting power

Model	RU-G3TB/5
Description	pocket transmitter
Carrier frequency range	506-542 MHz
Audio frequency range	50-18,000 Hz
Operating time	12 h
Transmitting power	10/50 mW
Power supply transmitter	2 x battery AA size, alkaline (not supplied)
Dimensions transmitter	62 x 80 x 23 mm
Weight transmitter	300 g
Connections transmitter	4-pole mini XLR

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



RU-901G3/5

Order No. 0259844

True diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET ULTRASONIC technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute
- LED for indicating RF level and AF level
- Backlit display with status indications, e.g. group/channel, frequency, battery, antenna A/B

Model	RU-901G3/5
Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-18,000 Hz
THD	< 0.6%
Dynamic range	105 dB
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 320 mV/600 Ω jack
Power supply receiver	via encl. power supply
Dimensions receiver	212 x 38 x 144 mm
Weight receiver	1.02 kg
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!



G3CH-2

Order No. 0259839

Charging station, for transmitters RU-G3TH/5, RU-G3TB/5, R-4TBM/5 and UF-20TB/5.

- For simultaneously charging rech. batteries of 2 devices
- Average charging time, depending on condition of rechargeable batteries used: approx. 5 hours
- Each slot with LED for indicating a fault and battery charging status
- Protection against overload, short-circuit and deep discharge

Model	G3CH-2
Description	charging station
Colour	black
Suitable for	transmitters RU-G3TH/5, RU-G3TB/5, R-4TBM/5, UF-20TB/5
Power supply	via encl. power supply
Dimensions	165 x 72 x 99 mm
Weight	323 g

- Mechanical reverse polarity protection
- Power is provided via enclosed power supply
- Dimensions: 165 x 72 x 99 mm

Supplied w/o devices

