

## MH-8800G/5

Order No. 0255450

### Dynamic hand-held UHF PLL transmitter

- Preset technology for easy configuration (64 channels)
- Pilot tone technology
- Adjustable sensitivity (0 dB to -30 dB)
- Lock function
- Special design to reduce handling noise, structure-borne noise and acoustic feedback
- Robust body
- Integrated LCD with battery status indication
- Supplied with robust transport case, colour-coded ID rings and stand clamp

Model	MH-8800G/5
Polar pattern	hypercardioid
System	dynamic
Carrier frequency range	518-542 MHz
Transmitting power	50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	> 25 h
Audio frequency range	50-16,000 Hz
Dimensions	Ø 53 mm x 245 mm
Weight	370 g

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



## PT-920BG/5

Order No. 0255490

### UHF PLL pocket transmitter with lavalier microphone

- Suitable for instrument microphones of the CX series and headband microphones or lavalier microphones from the CX/CM series
- Supplied with lavalier microphone CM-501
- 64 preset channels
- Pilot tone technology
- Continuously adjustable gain
- Lock function
- Integrated LCD for indicating battery status and transmission data
- Supplied with belt bag and robust transport case

Model	PT-920BG/5
Description	pocket transmitter
Carrier frequency range	518-542 MHz
Audio frequency range	40-18,000 Hz
Operating time	> 30 h
Transmitting power	10 mW
Power supply transmitter	2 x batt. AA size, alkaline (not supplied)
Dimensions transmitter	70 x 190 x 30 mm
Weight transmitter	130 g
Connections transmitter	4-pole mini XLR

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**



## US-903DCPRO/5

Order No. 0255570

### 2-channel diversity UHF PLL receiver

- 2 x 64 channel presets in four groups
- Parallel operation of up to 8 frequencies (equivalent to 4 x 2-channel system)
- Pilot tone squelch and adjustable noise squelch
- Lock function
- Backlit LCD for indicating status, e.g. for channel/group assignment and RF level/AF level
- Integrated charging slot for 4 x rechargeable NiMH battery AA size with indication of operating status
- Robust desktop metal housing
- Power supply for optional antenna booster UB-9001 directly via antenna inputs
- 482 mm (19") rack installation with supplied mounting brackets

Model	US-903DCPRO/5
Description	receiver unit
Carrier frequency range	518-542 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	40 mV XLR, 250 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	420 x 50 x 230 mm
Weight receiver	2.25 kg
Connections receiver	2 x XLR, bal. 1 x 6.3 mm jack, unbal.

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!**

