

MH-850/1

Order No. 0254460

Dynamic hand-held UHF PLL microphone transmitter

- 16 channels
- Pilot tone technology
- Special design to reduce handling noise, structure-borne noise and acoustic feedback
- Integrated low battery alert

Licence-free in the EU.

Model	MH-850/1
Polar pattern	hypercardioid
System	dynamic
Carrier frequency range	863-865 MHz
Transmitting power	10 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	25 h max.
Audio frequency range	50-16,000 Hz
Dimensions	Ø 55 mm x 260 mm
Weight	250 g



US-8001D/1

Order No. 0254480

Diversity UHF PLL receiver

- 16 channels
- Parallel operation of up to 4 intermodulation-free frequencies
- Pilot tone squelch and fixed noise squelch
- LEDs for indicating diversity status and AF level
- 482 mm (19") unit holder DR-900SET for 1 RU rack installation of 2 x US-8001D/1 is available at option

Licence-free in the EU.

Model	US-8001D/1
Description	receiver unit
Carrier frequency range	863-865 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	40 mV XLR, 150 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 170 mm
Weight receiver	455 g
Connections receiver	1 x XLR, bal., 1 x 6.3 mm jack, unbal.



US-8002D/1

Order No. 0254490

Diversity UHF PLL receiver

- 2 x 16 channels
- Parallel operation of up to 4 intermodulation-free frequencies
- Pilot tone squelch and fixed noise squelch
- LEDs for indicating diversity status and AF level
- 482 mm (19") unit holder DR-900SET for 1 RU rack installation of 2 x US-8002D/1 is available at option

Licence-free in the EU.

Model	US-8002D/1
Description	receiver unit
Carrier frequency range	863-865 MHz
Audio frequency range	40-18,000 Hz
THD	< 0.6%
Dynamic range	> 105 dB
Audio signal receiver	40 mV XLR, 150 mV jack
Power supply receiver	via encl. power supply
Dimensions receiver	210 x 40 x 170 mm
Weight receiver	500 g
Connections receiver	2 x XLR, bal., 1 x 6.3 mm jack, unbal.

