



CS-W4C/5

Order No.: 1000017

PRODUCTINFOS

4-channel diversity UHF PLL wideband receiver for conference system

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- RF output and mains voltage output for easily cascading up to 10 x CS-W4C/5 receiver without additional splitter
- REMOSET technology for receiver/transmitter synchronisation
- Removable antennas (BNC connection)
- Auto-scan function
- Pilot tone squelch and noise mute
- Volume settings to be selected for each channel
- Conference-specific priority settings
- Conference modes: override, priority and open mode
- Backlit display for indicating the status, e.g. for group/channel, frequency, battery, antenna A/B
- LED for indicating RF level and AF level
- Display for indicating battery status of the transmitters
- Power supply for optional antenna booster
- Link connections
- Trigger output

- XLR output per channel (bal.)
- XLR output (bal.) and 6.3 mm output for mixed signal
- Outputs mic/line, switchable
- 482 mm (19") rack installation, 1 RU

There are restrictions and requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

TECHNICAL SPECIFICATIONS

CS-W4C/5

General information

Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	60-16,000 Hz
Channels	4
THD	< 0.6%
Dynamic range	> 105 dB(A)
Admiss. ambient temp.	0-40 °C
Specifications transmitter	
Specifications receiver	
Audio signal receiver	630 mV/600 Ω XLR (line), 63 mV/600 Ω XLR (mic), 316 mV/600 Ω jack
Power supply receiver	~ 110-240 V/50-60 Hz/20 VA
Width receiver	485 mm
Height receiver	45 mm
Depth receiver	260 mm
Weight receiver	2.4 kg
Connections receiver	5 x XLR, bal., 1 x 6.3 mm jack, unbal.