



TG-10STX/1

Order No.: 0173730

PRODUCTINFOS

16-channel PLL Tour Guide System, 863-865 MHz

- With extensive accessories
- Operating range: up to 60 m
- Parallel operation of up to three wireless transmitters
- Licence-free in the EU

16-channel PLL wireless transmitter

- 2 inputs (CH1/CH2) via rear comb. jacks, with level controls
- 1 input (CH3) via 6.3 mm mono jack
- Continuously adjustable headphone output
- 2 loop outputs
- Phantom power can be activated as required

Licence-free in the EU.

TECHNICAL SPECIFICATIONS

TG-10STX/1

General information

Description tour guide system wireless transmitter

Carrier frequency range 863-865 MHz

Audio frequency range 40-15,000 Hz

Channels 16

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Operating range 60 m

Power supply transmitter via encl. power supply

Width transmitter 214 mm

Height transmitter 45 mm

Depth transmitter 240 mm

Weight transmitter 1.3 kg

Connections transmitter 2 x comb. jack (input CH1/CH2),
1 x 6.3 mm mono jack (input CH3),
1 x 3.5 mm stereo jack (headphones),
2 x 6.3 mm mono jack (loop outputs)