



## CX-516W

Order No.: 0234630

### PRODUCTINFOS

#### Electret instrument microphone

- For sound pickup of accordions, pianos or wind instruments
- Well-balanced frequency response for a genuine and brilliant sound
- Structure-borne noise isolated cartridge
- Flexible gooseneck
- Quick-acting holder of special design
- 1.4 m cable with fitted 4-pole mini XLR plug for direct connection to an optional pocket transmitter from JTS or to the phantom power supply adapter/mixer PS-500
- Supplied in a robust transport case with windshield

### TECHNICAL SPECIFICATIONS

#### CX-516W

|                     |                       |
|---------------------|-----------------------|
| Description         | instrument microphone |
| Transmission method | cable                 |
| Polar pattern       | supercardioid         |

**CX-516W**

|                                |                             |
|--------------------------------|-----------------------------|
| System                         | electret                    |
| Audio frequency range          | 20-20,000 Hz                |
| Nominal impedance              | 220 $\Omega$ $\pm$ 30%      |
| Sensitivity                    | 4.5 mV/Pa                   |
| Max. sound pressure            | 130 dB                      |
| Power supply                   | pocket transmitter from JTS |
| Housing material               | plastic                     |
| Admiss. ambient temp.          | 0-40 °C                     |
| Weight                         | 55 g                        |
| Cable                          | 1.4 m                       |
| Connection                     | 4-pole mini XLR             |
| Packing dimensions (W x H x L) | 0.17 x 0.085 x 0.36 m       |
| Gross weight                   | 0.764 kg                    |
| Net weight                     | 0.54 kg                     |