



## CX-508

Order No.: 0234610

### PRODUCTINFOS

#### Electret instrument microphone

- For sound pickup of wind instruments
- Wide dynamic range
- Crystal-clear and crisp sound
- Integrated spring-type clamp to attach to a horn
- Robust gooseneck, can be turned by 230°
- Design of low structure-borne noise with a low susceptibility to wind noise
- 3.3 m cable with fitted 3-pole XLR phantom power supply adapter for connection to a corresponding microphone input
- Supplied in a robust transport case with windshield

### TECHNICAL SPECIFICATIONS

#### CX-508

|                     |                       |
|---------------------|-----------------------|
| Description         | instrument microphone |
| Transmission method | cable                 |
| Polar pattern       | cardioid              |

**CX-508**

|                                |                       |
|--------------------------------|-----------------------|
| System                         | electret              |
| Audio frequency range          | 50-18,000 Hz          |
| Nominal impedance              | 220 $\Omega$          |
| Sensitivity                    | 5 mV/Pa               |
| Max. sound pressure            | 130 dB                |
| Power supply                   | 48 V phantom power    |
| Housing material               | plastic               |
| Admiss. ambient temp.          | 0-40 °C               |
| Weight                         | 170 g                 |
| Cable                          | 3.3 m                 |
| Connection                     | 3-pole XLR            |
| Packing dimensions (W x H x L) | 0.17 x 0.085 x 0.37 m |
| Gross weight                   | 0.87 kg               |
| Net weight                     | 0.64 kg               |