



## CM-502G6B

Order No.: 0233950

### PRODUCTINFOS

#### Overhead hanging electret microphone

- For suspended installations, especially suitable for applications in which a direct microphonic effect is undesired for optical or operational reasons, e.g. sound pickup of choirs or on theatre stages or school stages
- Microphone cartridge with supercardioid polar pattern
- Integrated phantom power supply adapter
- Flexible alignment due to gooseneck
- Easy-to-replace cartridge unit
- Black (CM-502G...B) or white (CM-502G...W) version
- Supplied with windshield

#### Total length:

CM-502G6...: 180 mm

CM-502G12...: 320 mm

## TECHNICAL SPECIFICATIONS

### CM-502G6B

Description	overhead hanging microphone
Transmission method	cable
Polar pattern	supercardioid
System	electret
Audio frequency range	100-18,000 Hz
Nominal impedance	220 $\Omega$
Sensitivity	4 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 48 V, phantom power
Housing material	metal
Admiss. ambient temp.	0-40 °C
Weight	100 g
Cable	8 m
Connection	XLR, bal.
Packing dimensions (W x H x L)	0.095 x 0.065 x 0.38 m
Gross weight	0.41 kg
Net weight	0.28 kg