



JSS-4B/5

Order No.: 0259390

PRODUCTINFOS

Dynamic hand-held UHF PLL transmitter

- Dynamic microphone cartridge (cardioid polar pattern) with wide dynamic range
- Aluminium housing
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-15 dB to +15 dB)
- Lock/mute function
- 4-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

“It features good ergonomics, high-quality workmanship and a pleasant sound. I compared it with a Neumann KMS 104 Plus and the dynamic cartridge of the JSS-4B provides an amazingly close sound.”

How many wireless systems can be operated simultaneously?

With optimum local conditions, it is possible to operate 18 wireless systems R-4/5, R-4THA/5, JSS-4B/5, R-4TBM/5 simultaneously.

TECHNICAL SPECIFICATIONS

JSS-4B/5

Description	hand-held microphone
Transmission method	wireless
Polar pattern	cardioid
System	dynamic
Carrier frequency range	506-542 MHz
Transmitting power	10/50 mW
Power supply	2 x batt. AA size, alkaline (not supplied)
Operating time	> 20 h
Audio frequency range	50-18,000 Hz
Max. sound pressure	150 dB
Housing material	aluminium
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 50 mm x 253 mm
Weight	335 g
Packing dimensions (W x H x L)	0.3 x 0.08 x 0.1 m
Gross weight	0.63 kg
Net weight	0.385 kg