



## R-4/5

Order No.: 0259400

### PRODUCTINFOS

#### 4-channel diversity UHF PLL wideband receiver

- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- RF output and mains voltage output for easily cascading up to 10 x R-4/5 receiver without additional splitter
- REMOSET technology for receiver/transmitter synchronisation
- Auto-scan function
- Pilot tone squelch and noise mute
- LED for indicating RF level and AF level
- Backlit display for indicating battery status of the transmitter, frequency setup, active antenna
- XLR output per channel, bal.
- XLR output and 6.3 mm output for mixed signal
- Switchable mic/line for single outputs and mixed outputs
- Metal housing

**There are restrictions or requirements within the EU!**

**Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!**

### **tools4music 02/2019**

“The wireless 4-channel diversity UHF system from JTS is a special highlight in MONACOR INTERNATIONAL's portfolio. If you are not fixated on big brands, you should definitely take a closer look at this system and listen to it. Many small but significant features of this system certainly indicate that JTS is also aiming at professionals.”

- + highly practical features
- + sound
- + excellent workmanship

### **How many wireless systems can be operated simultaneously?**

With optimum local conditions, it is possible to operate 18 wireless systems R-4/5, R-4THA/5, JSS-4B/5, R-4TBM/5 simultaneously.

## **TECHNICAL SPECIFICATIONS**

### **R-4/5**

General information

Description wireless receiver

Carrier frequency range 506-542 MHz

Audio frequency range 50-18,000 Hz

Channels 4

THD < 0.6%

Dynamic range > 105 dB

Admiss. ambient temp. 0-40 °C

Specifications receiver

Audio signal receiver 630 mV/600 Ω XLR (line),

63 mV/600 Ω XLR (mic),  
320 mV/600 Ω jack

Power supply receiver ~ 100-240 V/50-60 Hz

Width receiver 485 mm

Height receiver 44 mm

Depth receiver 230 mm

Weight receiver 2.65 kg

Connections receiver 4 x XLR, bal.,  
1 x XLR, bal., 1 x 6.3 mm jack (mixed out)

