



R-4TBM/5

Order No.: 0259841

PRODUCTINFOS

UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (± 15 dB)
- Lock function
- 6-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

How many wireless systems can be operated simultaneously?

With optimum local conditions, it is possible to operate 18 wireless systems R-4/5, R-4THA/5, JSS-4B/5, R-4TBM/5 simultaneously.

TECHNICAL SPECIFICATIONS

R-4TBM/5

General information

Description pocket transmitter

Carrier frequency range 506-542 MHz

Audio frequency range 50-18,000 Hz

Channels 1

Operating time > 20 h

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Transmitting power 10/50 mW

Operating range 120 m

Power supply transmitter 2 x batt. AA size (not supplied)

Width transmitter 62 mm

Height transmitter 80 mm

Depth transmitter 23 mm

Weight transmitter 95 g

Connections transmitter 4-pole mini XLR