



UF-20TB/5

Order No.: 0257230

PRODUCTINFOS

The wideband multifrequency system UF-20... from JTS

is the perfect solution for stage applications of high requirements due to an excellent flexibility and reliability.

The device impresses with a convenient setup function, REMOSET technology, 75 MHz bandwidth, 3,000 frequencies which can be selected as desired and additional professional features, e.g. active carrier analysis method.

UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 75 MHz
- 15 groups, each with up to 63 compatible preset channels
- 64 channels in 6 groups from 3,000 selectable individual frequencies can be stored in user presets
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (-18 dB to +12 dB)
- Lock function
- 5-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

tools4music 06/2015

"With the wireless system UF-20, JTS is able to offer an absolutely professional system. Despite numerous features, the menu navigation can easily be followed and understood. The REMOSET function allows you to simultaneously adjust up to 48 transmitters and receivers. In addition, important functions of the hand-held transmitter can remotely be controlled via the receiver which is particularly helpful at festivals. It allows you to quickly adjust the microphone sensitivity. The system also impresses with an appealing design and a neat workmanship."

TECHNICAL SPECIFICATIONS

UF-20TB/5

General information

Description pocket transmitter

Carrier frequency range 530-605 MHz

Audio frequency range 50-18,000 Hz

Channels 1

Operating time > 20 h

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Transmitting power 10/50 mW

Power supply transmitter 2 x batt. AA size (not supplied)

Width transmitter 62 mm

Height transmitter 170 mm

Depth transmitter 23 mm

Weight transmitter 90 g

Connections transmitter 4-pole mini XLR