



US-36G2/5

Order No.: 0257300

PRODUCTINFOS

True diversity UHF PLL receiver

- 124 channels in six groups, up to 22 channels per group, 1,441 individual frequencies can be selected
- Pilot tone and noise squelch, squelch can be adjusted
- Auto-scan
- Lock function
- LCD for indicating group/channel, frequency, antenna A/B, squelch, battery status (transmitter) and an additional LED level display for AF/RF signal
- XLR output, bal.
- 6.3 mm jack output
- Robust metal housing
- Supplied with power supply
- Power supply for antenna booster UB-900I directly via antenna terminals

There are restrictions or requirements within in the EU!

Please read the notes regarding wireless systems in the section "IMPORTANT INFORMATION"!

SOUNDCHECK 04/2017

“Transmitting like professionals ... the intuitive operation of this clearly arranged system combined with an excellent technical performance and versatile transmission options make the wireless system US-36G2/5 from JTS an ideal solution for stage and all other applications where speech or vocals are to be transmitted in professional quality. With an excellent sound quality, low susceptibility to acoustic feedback and a reliable wireless signal, this system is a viable alternative for many microphone applications which previously required wired microphones.”

TECHNICAL SPECIFICATIONS

US-36G2/5

General information

Description	receiver unit
Carrier frequency range	506-542 MHz
Audio frequency range	50-18,000 Hz
Channels	1
THD	< 0.6%
Dynamic range	> 105 dB
Admiss. ambient temp.	0-40 °C
Specifications receiver	
Audio signal receiver	120 mV XLR, bal. 70 mV jack, unbal.
Power supply receiver	via encl. power supply
Width receiver	211 mm
Height receiver	40 mm
Depth receiver	145 mm
Weight receiver	1 kg
Connections receiver	XLR, bal. 6.3 mm jack, unbal.