



CM-214F

Order No.: 0236430

PRODUCTINFOS

Electret headband microphone

- Omnidirectional polar pattern allows for microphone to be positioned slightly next to the mouth in an unobtrusive way instead of directly in front of the mouth
- · Ultra-light and adjustable headband
- Replaceable connection cable
- Secure fit, very comfortable to wear
- Drip ring protects cartridge from moisture and ensures a long operating life
- For connection to the pocket transmitters of the IN/PT/UF series with 4-pole mini XLR connection cable
- Connection cable 801TG with 3.5 mm plug for use with our tour guide systems is available at option
- Supplied with bag and windshield

TECHNICAL SPECIFICATIONS

CM-214F Description Transmission method Polar pattern

headband microphone cable omnidir.



www.jts-europe.com

CM-214F - Page: 2

CM-214F

System	electret
Audio frequency range	60-15,000 Hz
Nominal impedance	2.2 kΩ
Sensitivity	10 mV/Pa
Max. sound pressure	130 dB
Power supply	pocket transmitter IN/PT/UF series or PS-500
Admiss. ambient temp.	0-40 °C
Weight	40 g
Connection	cable with 4-pole mini XLR (optional 3.5 mm stereo plug, 3-pole mini XLR or 4-pole Hirose connector)
Packing dimensions (W x H x L)	0.145 x 0.1 x 0.185 m
Gross weight	0.184 kg
Net weight	0.046 kg