



CM-214ULF

Order No.: 0236450

PRODUCTINFOS

Electret headband microphone

- Transparent sound
- Adjustable headband, comfortable to wear
- Highly resistant to acoustic feedback due to cardioid polar pattern
- Replaceable connection cable
- Flexible cartridge arm for exact positioning of cartridge, thus providing an optimum sound with an unobtrusive appearance
- Connection cable with strain relief, screwed-on
- Integrated drip ring protects the cartridge from moisture
- Supplied with a 4-pole mini XLR connection cable for connection to pocket transmitters of the IN/PT/UF series
- Connection cable 801TG with 3.5 mm plug for use with our tour guide systems is available at option
- Supplied with bag and windshield

TECHNICAL SPECIFICATIONS

CM-214ULF

Description	headband microphone
Transmission method	cable
Polar pattern	cardioid
System	electret
Audio frequency range	100-18,000 Hz
Nominal impedance	1.5 kΩ
Sensitivity	1.8 mV/Pa
Max. sound pressure	120 dB
Power supply	pocket transmitter IN/PT/UF series or PS-500
Admiss. ambient temp.	0-40 °C
Weight	44 g
Connection	4-pole mini XLR (optional: 3.5 mm stereo plug, 3-pole mini XLR or 4-pole Hirose connector)
Packing dimensions (W x H x L)	0.145 x 0.1 x 0.185 m
Gross weight	0.189 kg
Net weight	0.048 kg