



## IT-12D

Order No.: 0173710

### PRODUCTINFOS

#### **Interpretation console,**

as an addition to the base unit IT-12M.

- Up to 11 interpretation consoles can be cascaded
- 2 channels, one of which is active, the other serves as a standby channel
- Interpreting channels can be stored permanently at the console
- Last active channel will be stored after switching off the operating voltage and will be available again immediately after switching on the unit
- 2 simultaneous interpreters/commentators to use the active channel at the same time
- Headset connection with volume control
- Microphones can be switched off or muted, cough button
- Balanced XLR jacks for connecting additional microphones
- Relay interpreting via 11-step language selector
- Low-noise push-buttons for switching between relay language and floor language
- Protocol of interpretation via 2 record outputs
- Slow-down button
- Robust and stable metal housing
- Power supply via base unit
- Dimensions: 330 x 56 x 206 mm
- Weight: 2.3 kg

## TECHNICAL SPECIFICATIONS

### IT-12D

Description	interpretation console
Type	2 channels
Colour	black
Material	metal
Suitable for	IT-12M
Power supply	via IT-12M
Dimensions	330 x 56 x 206 mm
Weight	2.3 kg
Connections	headset connection, bal. XLR jacks, record outputs
Packing unit	1
Packing dimensions (W x H x L)	0.45 x 0.305 x 0.15 m
Gross weight	3.59 kg
Net weight	2.84 kg