



TG-98TA/5

Order No.: 0257410

PRODUCTINFOS

Professional PLL Tour Guide System

- Bandwidth: 36 MHz
- 6 groups with up to 22 channels
- 124 channels
- 506-542 MHz
- Operating range: up to 200 m
- Operating time: approx. 10 hours
- There are restrictions or requirements within the EU!

Professional PLL pocket transmitter

- Built-in electret microphone
- 3.5 mm microphone connection
- Supplied with matching electret tie clip microphone
- Audio input via 3.5 mm jack
- LCD for indicating channel/group, RF, mute and battery status
- Lock function
- Mute function

- Volume level control
- Selectable transmitting power
- Belt clip and lanyard
- Parallel operation possible of up to 22 transmitters max.
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

TECHNICAL SPECIFICATIONS

TG-98TA/5

General information

Description tour guide system pocket transmitter

Carrier frequency range 506-542 MHz

Audio frequency range 40-18,000 Hz

Channels 124

Admiss. ambient temp. 0-40 °C

Specifications transmitter

Operating range 200 m

Power supply transmitter 2 x 1.2 V NiMH rech. batt. AA size (not supplied)

Width transmitter 62 mm

Height transmitter 112 mm

Depth transmitter 28 mm

Weight transmitter 72 g

Connections transmitter 1 x 3.5 mm jack (microphone),
1 x 3.5 mm jack (audio input)